

Office of the Nodal Officer
 Community College
 (B.VOC – Programme)

Dated. 04/01/2017

No.....

M/s.....

Dear Sirs,

Sealed quotations/tenders are invited for the following articles on the terms and conditions printed over-leaf.

Quotations should reach this office on or before 24/01/2017 at 3:00 am/pm.

S.No.	Approximate Quantity needed	Particulars / Specifications
1.	One	<p>ELECTRIC DISCHARGE MACHINE (EDM) SPECIFICATIONS:</p> <ol style="list-style-type: none"> 1. X, Y, Z : 280 x 200 x 250 mm 2. Work Tank : 725 x 415 x 315 mm 3. DC Servo with speed-up function 4. Z Axis NC 5. Integral design with compact footprint 6. NRB for co-ordinate table 7. Ergonomically designed control panel 8. Day/Night mode for 24 hours operation 9. Reverse servo for reverse sparking 10. Reverse polarity for easy operation <p>*Complete setup in all respect (Essentials and Optional Accessories as Servo Stabilizer, Dielectric fluid, Megnetic V-Block and additional Electrodes)</p>
2.	One	<p>ELECTRIC DISCHARGE MACHINE (EDM) SPECIFICATIONS:</p> <ol style="list-style-type: none"> 1. X, Y, : 300 x 200 mm 2. Z : 200 mm 3. Work tank : 800x500x325 4. Work table : 550 x 350 mm 5. Max. job HT : 275 mm 6. Day light (with electrode holder) : 295 mm 7. Shut height : 95 mm 8. Max. Workpiece weight : 300 kg. 9. Die Electric tank : 170 ltr. 10. Machine floor Area : 1500x1200x2000 mm 11. Pulse generator : ZNC <p>*Complete setup in all respect (Essentials and Optional Accessories as Servo Stabilizer, Dielectric fluid, Megnetic V-Block and additional Electrodes)</p>

S.No.	Approximate Quantity needed	Particulars / Specifications																																							
3.	Two	<p><u>ALL GEARED LATHE MACHINE :</u></p> <p>SPECIFICATIONS:</p> <table border="0"> <tr><td>1. Distance b/w Centres</td><td>:</td><td>750/1000 mm</td></tr> <tr><td>2. Centre Height</td><td>:</td><td>200 mm</td></tr> <tr><td>3. Swing over Bed</td><td>:</td><td>402 mm</td></tr> <tr><td>4. Swing over Gap</td><td>:</td><td>560 mm</td></tr> <tr><td>5. Gap length</td><td>:</td><td>120 mm</td></tr> <tr><td>6. Bed Width</td><td>:</td><td>250 mm</td></tr> <tr><td>7. Swing over Carriage</td><td>:</td><td>380 mm</td></tr> <tr><td>8. Cross Slide Travel</td><td>:</td><td>240 mm</td></tr> <tr><td>9. Head Stock spindle bore</td><td>:</td><td>42 mm</td></tr> <tr><td>10. Speed Range</td><td>:</td><td>40 – 2800 RPM</td></tr> <tr><td>11. Power</td><td>:</td><td>4 kW</td></tr> </table>	1. Distance b/w Centres	:	750/1000 mm	2. Centre Height	:	200 mm	3. Swing over Bed	:	402 mm	4. Swing over Gap	:	560 mm	5. Gap length	:	120 mm	6. Bed Width	:	250 mm	7. Swing over Carriage	:	380 mm	8. Cross Slide Travel	:	240 mm	9. Head Stock spindle bore	:	42 mm	10. Speed Range	:	40 – 2800 RPM	11. Power	:	4 kW						
1. Distance b/w Centres	:	750/1000 mm																																							
2. Centre Height	:	200 mm																																							
3. Swing over Bed	:	402 mm																																							
4. Swing over Gap	:	560 mm																																							
5. Gap length	:	120 mm																																							
6. Bed Width	:	250 mm																																							
7. Swing over Carriage	:	380 mm																																							
8. Cross Slide Travel	:	240 mm																																							
9. Head Stock spindle bore	:	42 mm																																							
10. Speed Range	:	40 – 2800 RPM																																							
11. Power	:	4 kW																																							
4.	Two	<p><u>ALL GEARED LATHE MACHINE :</u></p> <p>SPECIFICATIONS:</p> <table border="0"> <tr><td>1. Admit b/w Centres</td><td>:</td><td>1000 mm</td></tr> <tr><td>2. Centre Height</td><td>:</td><td>175 mm</td></tr> <tr><td>3. Swing over Bed</td><td>:</td><td>350 mm</td></tr> <tr><td>4. Swing over cross slide</td><td>:</td><td>215 mm</td></tr> <tr><td>5. Swing in gap</td><td>:</td><td>540 mm</td></tr> <tr><td>6. Head Stock spindle bore</td><td>:</td><td>41 mm</td></tr> <tr><td>7. Speed</td><td>:</td><td>08</td></tr> <tr><td>8. Speed Range</td><td>:</td><td>54 – 1200 RPM 67 – 1500 RPM</td></tr> <tr><td>9. Motor</td><td>:</td><td>1440 RPM, 3 phase 3 HP, AC</td></tr> <tr><td>10. Lead screw diameter</td><td>:</td><td>28 mm, Thread pitch 6 mm</td></tr> <tr><td>11. Tailstock diameter</td><td>:</td><td>50 mm</td></tr> <tr><td>12. Quill travel</td><td>:</td><td>140 mm</td></tr> <tr><td>13. Taper</td><td>:</td><td>MT-3</td></tr> </table>	1. Admit b/w Centres	:	1000 mm	2. Centre Height	:	175 mm	3. Swing over Bed	:	350 mm	4. Swing over cross slide	:	215 mm	5. Swing in gap	:	540 mm	6. Head Stock spindle bore	:	41 mm	7. Speed	:	08	8. Speed Range	:	54 – 1200 RPM 67 – 1500 RPM	9. Motor	:	1440 RPM, 3 phase 3 HP, AC	10. Lead screw diameter	:	28 mm, Thread pitch 6 mm	11. Tailstock diameter	:	50 mm	12. Quill travel	:	140 mm	13. Taper	:	MT-3
1. Admit b/w Centres	:	1000 mm																																							
2. Centre Height	:	175 mm																																							
3. Swing over Bed	:	350 mm																																							
4. Swing over cross slide	:	215 mm																																							
5. Swing in gap	:	540 mm																																							
6. Head Stock spindle bore	:	41 mm																																							
7. Speed	:	08																																							
8. Speed Range	:	54 – 1200 RPM 67 – 1500 RPM																																							
9. Motor	:	1440 RPM, 3 phase 3 HP, AC																																							
10. Lead screw diameter	:	28 mm, Thread pitch 6 mm																																							
11. Tailstock diameter	:	50 mm																																							
12. Quill travel	:	140 mm																																							
13. Taper	:	MT-3																																							